



SPECS

16' 6" LOA 10 Degree Deadrise 72" Beam 66" Bottom Width 24" Side Height

.190" 5086 Keel .125" 5052 Sides .190" 5086 Transom Maximum Horsepower 40hp Approximate Dry Weight 1,130lbs 45L Fuel Capacity

Engine & Controls

Mercury JET 40ELPT Stainless Steel Impeller

Hull

Full Length Box Stringers
Coyote Exclusive PrecisionCurve® Sides
Coyote Exclusive HR Tunnel Upgrade
Full Reverse Chines
Level Flotation Kit

Canvas & Exterior

Custom Billet Rope Cleats 4 Burnewiin GM400 Universal Mounts

Interior

Driver Seat/ Pedestal w/ Slider Raised Front Deck Single Hatch for Semi-Dry Bow Storage Vinyl Covered Floor Boards 2 Cup Holders

Systems

Marine Grade Wiring Harness / Fuse Block LED Navigation Lights Auto Bilge Pump Electric Horn Dual Battery Ready

Trailer

Highliner 1,700lb Galvanized Trailer w/ Swing

Engine & Controls

Smartcraft Engine Monitoring Gauge Tilt Steering Tiller Configuration (Removes Centre Console)

Hull

4'x 10' .375" UHMW Hull Protection w/ Stainless Fasteners Intake Protection Bars

Canvas & Exterior

Bimini Top Travel Cover (Center Console / Windshield Required) Glass Windshield Kit Padded Windshield Cover

Interior

AVAILABLE

UltraDeck Premium Gunnel & Flooring Options Driver's Seat Box Storage (Centre Console Required) 32" Storage Box/Seat (Centre Console Required)

Paint & Finishing

Coyote Coat Interior & Full Side Paint